



Technical data **MobiSCREEN**

Display size	2 x 18.5"	29"
Format	2 x 16:9	16:5
Resolution	2 x 1366 x 768 (WXGA)	1920 x 610 (Full HDxn)
Brightness	min. 300 Nits	min. 400 Nits
Weight	approx. 12 kg	approx. 10 kg
Power consumption	max. 33,6 W	max. 48 W
Contrast	3,000:1	
Viewing angle	178°/178°	
Colours	16.7 million, 24 Bit	
Housing	anodised aluminium	
Operating voltage	24 VDC (16.8 - 32 VDC)	
Operating temperature	0 °C to +50 °C (Security switch-off outside this range)	
Interfaces	IP/Ethernet, USB optional: RS485, IBIS	
Editing software	MCE (Mobitec Content Editor) and MAW (Mobitec Access Web)	
Data and firmware update	manually from USB flash memory automatically via IP/Ethernet Interface with MAW (Mobitec Access Web)	
Operating system	Linux	
Standards and directives	ECE-R10, (EMC-Bus)	

Compact TFT screen with elegant aluminium profile.

Vandal-proof design with toughened safety glass.

Can display different kinds of information:

- Next stop
- Detailed route information with connections
- Network map
- Newsticker
- Advertisement (text, video and image) as additional source of income

Route information and advertisements can be displayed simultaneously.

Customised layout in your corporate design possible.

LED backlight.

Low weight.

Flexible mounting concept.

Low maintenance: no moving parts, fanless heat management.

29": Screen can be split in customised ratio or used as full screen.